

3 STRAND SUPERLINE



Features:

- ◆ 80% higher tensile strength than Mono-Polypropylene
- ◆ Higher abrasion resistance than Mono-Polypropylene
- ◆ 16% - 18% stretch, which is less than Mono-Polypropylene
- ◆ Approximate strength of Nylon rope
- ◆ Less stretch than Nylon rope
- ◆ Extremely UV resistant
- ◆ No loss of strength when wet
- ◆ Resists rot and mildew, stores wet
- ◆ Excellent resistance to acids and alkalis
- ◆ Floats (S.G. = 0.94)

Construction:

- ◆ Three strand rope with co-polymer fibres of Polyethylene & Polypropylene
- ◆ Mono-filament yarns
- ◆ Light green in colour
- ◆ Other Colours Available: yellow & black w/ red tracer

Applications:

- ◆ Anywhere Mono-Polypropylene is used and where a greater strength and abrasion resistance is required, without the expense of Nylon or Polyester ropes.

Product Code	Size Inches	Size mm	Tensile* Lbs	L.D. Lbs/ Kft
SL14	1/4"	6.4	1653	12.6
SL516	5/16"	7.9	2976	19.6
SL38	3/8"	9.5	4519	31
SL12	1/2"	12.7	6614	49.3
SL58	5/8"	15.9	10200	79
SL34	3/4"	19.1	13448	109.6
SL78	7/8"	22.2	20503	148.8
SL1	1"	25.4	23149	184
SL118	1 1/8"	28.6	31967	244.2
SL114	1 1/4"	31.8	36376	299.4
SL1516	1 5/16"	33.3	40786	331.6
SL112	1 1/2"	38.1	51368	434
SL158	1 5/8"	41.3	61729	508.8
SL134	1 3/4"	44.5	74957	595.4
SL2	2"	50.8	87083	771.1

* Average Tensile Strengths, consult **MCM Ropes** if safety becomes an issue *



Professional Engineers
Ontario



MCM ROPES & RIGGING LTD.

