

KNOTLESS SUPERLINE VERTICAL LIFELINE ROPE

Knotless Superline



Tracer in each Strand



Z259.2.1

- **Lifeline** must be free of knots or splices except at termination
- **Lifeline** must be of synthetic fibre or wire rope
- **Lifeline** must have a breaking strength of not less than 27 kN (6067 Lbs)
- **Lifeline** termination must not reduce the strength of the rope to below 22 kN (4943 Lbs)
- **Lifeline** of synthetic rope to have no more than 22% elastic elongation a 8

Size Inches	Size mm	* Tensile Lbf	Tensile kN	L.D. Lbs/Kft	L.D. Kg/Km
5/8	16	10,200	47	85.8	127.6518

* Average Tensile Strengths, consult **MCM Ropes** if after safety factor strength is still an issue.

A New Superior Vertical Lifeline Rope

- Continuous filament yarn production means no splices or knots in this rope, certified to **C.S.A.** specifications
- UV inhibitors added to fibres
- Twice the strength of regular Polypropylene
- Higher abrasion resistance than Mono-Polypropylene
- 16% - 18% stretch, which is less than Mono-Polypropylene
- Approximate strength of Nylon rope
- Less stretch than Nylon rope
- Extremely UV resistant
- No loss of strength when wet
- Resists rot and mildew, stores wet
- Excellent resistance to acids and alkalis
- Floats (S.G. = 0.94)



Professional Engineers
Ontario



www.mcmropes.com

